



**RUST-OLEUM® RUST-O™  
ARTIST SPRAY PAINT**

**DESCRIPTION AND USES**

Rust-O™ Spray Paint by Rust-Oleum® is designed with the artist in mind. It is a highly pigmented lacquer that delivers clean lines, quick fills, and smooth shading. Spray from less than an inch away for thin lines or pull back for broad areas. Rust-O is ideal for painting concrete, brick, wood, metal, most plastic, canvas, wicker and more. It dries fast and resists sags and drips, giving you the freedom to work at the speed of your hand. The UV resistance helps keep your artwork colors from fading.

Donut ring indicates color of paint. Remove the smaller over cap for use; replace in between uses to prevent accidental spray.

**TIP:** Plastics made of polyethylene are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first.

**PRODUCTS**

SKU	DESCRIPTION (11 oz. Aerosol)
392198	Matte White Noise
392199	Matte Cloudy Daze
392200	Matte Comic Blue
392201	Matte Sodalite
392202	Matte Deep Abyss
392203	Matte Peacock
392204	Matte Wilderness
392205	Matte Hint of Mint
392206	Matte Lucky Charm
392207	Matte Grass Stain
392208	Matte Banana Whip
392209	Matte Gumball
392210	Matte Taxi
392211	Matte Sun Kissed
392212	Matte Ghost Pepper
392213	Matte Sunstone
392214	Matte Piggy Bank
392215	Matte Cactus Flower
392216	Matte Carnivale
392217	Matte Blood Rose
392218	Matte Berry Punch
392219	Matte Violet Underground
392220	Matte Grape Lollipop
392221	Matte Pixie Dust
392222	Matte Duck Egg
392223	Matte Space Dust
392224	Matte Coal Chute
392225	Matte Treasure Map
392226	Matte Bittersweet
392227	Matte Mix Tape
398670	Matte Aurora Glow
398671	Matte Purpletop
398673	Matte Indigo Milk
398674	Matte Foggy Morn
398675	Matte Matcha Sand
398676	Matte Cacao Supremo
393872	12 Ct. Mixed Color Spray Pack

**COMPANION PRODUCTS**

SKU	DESCRIPTION
394191	6 Ct. Spray Cap Accessory Pack

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove loose paint and rust with wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry.

**WARNING!** If you scrape, sand, or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION**

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not use on objects that may exceed 200°F (93°C) surface temperature. Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, **DO NOT STRIKE CAN.** Contact Rust-Oleum. Shake often during use. Greater variation in spray patterns can be obtained using our Spray Cap Accessory Pack 394191.

**DRY & RECOAT**

Dry and recoat times are based on 70-80°F (21-27°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 20 minutes, to handle in 1 hour and fully dry in 24 hours. Can be re-coated at any time.

**CLEANUP**

Wipe off tip before storing. Clean up wet paint with Xylol or mineral spirits. Throw away or recycle empty can in accordance with local laws. Do not burn or place in home trash compactor.

**CLOGGING**

Clean spray valve by turning can upside down and pushing spray button for 5 seconds.



**RUST-OLEUM® RUST-O™  
ARTIST SPRAY PAINT**

**PHYSICAL PROPERTIES**

		RUST-O ARTIST SPRAY PAINT
<b>Resin Type</b>		Acrylic
<b>Pigment Type</b>		Varies with Color
<b>MIR</b>		0.80 Max
<b>Fill Weight</b>		11oz.
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		N/A
<b>Practical Coverage at Recommended DFT (assume 15% material loss)</b>		Approximately 10 - 12 sq ft./can (0.92 - 1.11 m <sup>2</sup> /can)
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Recoat</b>	Anytime
	<b>Touch</b>	20 minutes
	<b>Handle</b>	1 hour
	<b>Fully Dry</b>	24 hours
<b>Dry Heat Resistance</b>		N/A
<b>Shelf Life</b>		5 Years
<b>Flash Point</b>		-42°F (-41°C)
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

